



**wePresent WiPG**  
Wireless interactive Presentation Gateway



# WiPG-1000

## Wireless interactive Presentation Gateway

Link PC, Mac, Pad, Mobile, Projector or Display all together to make professional and interactive presentation.

(Full HD Support)



## Revolutionary “interactive” features and “Mobile” application

### ■ Remote Desktop Support

Use a set of mouse and keyboard connected to WiPG-1000 to control the projecting PC/Mac.

### ■ SidePad

Use iPad/iPhone or Android Pad/Phone to control the projecting PC/Mac.

### ■ BrowserSlides

Allow audience to use web browser to view the speaker’s slides and save them for taking notes.

### ■ Two-way Wireless Projection Control

Select a PC/Mac from WiPG starting screen or its web page to make projection

### ■ WiFi-Doc

Project MS-office file (doc, xls, ppt) & PDF document from iPad/iPhone or Android Pad/Phone

### ■ IWB-Intelligent White Board Support (selected model)

Speaker and audience interact on IWB wirelessly

## Enhanced features

### ■ Full HD Support

Support video output up to 1920x1080 through HDMI, 1600x1200 through VGA interfaces

### ■ FPNs Plus

Fast Plug&Show+ with 30 FPS & audio projection for Win XP/Vista/7 & Mac

### ■ 4-to-1 Plus

30 FPS quadrant screen projection for Win XP/Vista/7 & Mac

### ■ Conference control Plus

Web-based mediator function and new standby screen PC-list design



## Basic features

Windows/Mac support

MobiShow for iOS/Android/Blackberry

Plug&Show: launching the projection application from a USB thumb drive

4-to-1 Quadrant Screen Projection

SNMP Manager: manage/configure multiple WiPGs thru SNMP consoles

Conference Control: Mediator control function thru the device web page

Support up to 64 logged users

Security design: Session Login Code, WEP/WPA key, and GateKeeper

HDMI and VGA dual video interfaces

WiFi AP-Client mode support

WiFi 802.11b/g/n

## Specification

Standards	IEEE 802.11b/g/n 2.4GHz IEEE 802.3 (10BASE-T) / IEEE 802.3u (100BASE-TX)
Security	IEEE Standard 64/128 bit WEP / WPA / WPA2-PSK
Management	Web-based configuration
Supported Output Resolution	VGA:SVGA(800x600)/XGA(1024x768) /WXGA(1280x768)/WXGA(1280x800)/WXGA(1360x768) / WXGA+(1440x900)/UXGA(1600x1200) HDMI:720p(1280x720)/1080p(1920x1080)
Supported Operation System	Windows XP / Vista / 7, Mac OS X 10.5 and above, Android 2.2 and above, iOS 3.2 and above.
Power	External power adaptor DC 5V 2.6A
Interfaces	15Pin VGA HDMI RJ-45 USB 2.0 x 3 Power Button Reset Button Stereo Phone Jack
Certificate	FCC/CE